



Outdoor wall mount Mini PTZ Dome



WPTM-500-10X

FEATURES

- ◆ Integrated and convenience installation structure.
- ◆ Built-in zoom with 100 times (10x optical, 10 x digital).
- ◆ Horizontal resolution: 500TVL/570TVL (optional);
- ◆ Mini illumination: 0.02Lux.
- ◆ Built-in shock absorber.
- ◆ Screen will display pan/ tilt position, zoom etc.
- ◆ Communication: RS485/SDLC/COAX.
- ◆ IP66 all-day defend cover.
- ◆ Built-in TVS1500W lightning-proof, surge-proof and wave-proof.
- ◆ Pan 360°, Tilt 90° continuously rotation with auto-flip, humanize focus and speed proportion.
- ◆ Park action function, can auto-call presets or start-up tour, pattern, scan and display areas after dome idle for a period of time.
- ◆ Built-in OSD menu, can change information and parameter of dome through menu, also can set and call the presets, tour, scan, pattern, camera mode and display name etc.
- ◆ 128 presets(titles can be set), 4 tours; 8 programmable zones(titles can be set); 4 pattern, each record time is more than 180 seconds; 4 scan, support camera scanning repeatedly between right limit and left limit at an appointed speed.

Authorized Dealer:

Specifications

Scanning system	NTSC/PAL 2:1 interlacing
Imaging element	1/4 inch Super HAD CCD
Significant pixel (HxV)	752(H)X582(V)
Resolution	500TVL / 570TVL (Optional)
Video output	1.0±0.2Vp-p
S/N ratio (S/N)	50dB
Illumination	0.02 Lux
White balance	Auto/manual (R/B gain control)
Back-compensation	Off/auto with auto-flip
Focus	3.8 ~ 38mm
Electron Shutter	1/50 ~ 1/120,000s
Manual speed	Pan (0.5° ~ 160°/s)
	Tilt (0.5° ~ 90°/s)
Preset speed	320°/s
Rotation	Continuously 360°; tilt 0~90° with auto-flip
Speed Proportion	As the length of focus, to auto-adjust the speed
Zoom	Total zoom 100X (Optical 10X; Digital 10X)
Preset	128 preset, title can be edited
Auto-flip	Tilt down 90°, with auto-flip 180°
Scan	355°programmable, 4 scans
Display zone	8 programmable zones with titles
Sync model	Internal
Decoder	Built-in
Video output	Female BNC
Remote controlling	RS485/SDLC/COAX (Coaxial video control)
Baud rate (RS485)	2400 / 4800 / 9600 / 19200 bps
ID range	1 ~ 254
Temperature	0°C ~ +50°C
Humidity	0 ~ 95% (Non-condensation)
Protection grade	IP66, 1500w lightning-proof, surge-proof, all-day defend cover
Power supply	DC12V / AC 24V
Power consumption	<9W
Dimension	250x160x174 (H) mm (Model:D8407 Outdoor wall mount)
Net weight	2.3kg (with bracket)

All product specifications on this brochure are subject to change without notice.

Canada
 351 Ferrier Street, Unit 5
 Markham, ON
 L3R 5Z2
 Toll Free: 1-866-843-6865
 Tel: 416-410-6865
 Fax: 1-866-331-3341

USA
 275 Cooper Avenue, Suite 105
 Tonawanda, NY
 14150 USA
 Toll Free: 1-866-843-6865
 Local: 1-716-877-7277
 Fax: 1-866-331-3341