



**FILTER CHANGEABLE  
DAY & NIGHT  
VANDAL RESISTANT  
IR DOME CAMERA**



**DI-540NDV**

## FEATURES

- 540 TV Lines Horizontal Resolution
- Filter Changeable Day & Night
- Photo Sensor & IR LED (18pcs)
- Electronic IRIS
- Privacy Function
- 3 Axis built-in Vandal Resistant Dome Housing
- High Sensitivity
- DNR (Digital Noise Reduction)
- Controlled by OSD Menu
- Weather Proof (IP66)

## SPECIFICATIONS

	NTSC	PAL	
Power Consumption	Normal: 220mA, IR-LED On: 480mA (DC12V only)		
	Normal: 340mA, IR-LED On: 690mA (DC12V)		
	Normal: 340mA, IR-LED On: 690mA (DC12V)		
C C D	Total Pixels	811(H) x 508(V)	795(H) x 596(V)
	Effective pixels	768(H) x 494(V)	752(H) x 582(V)
S y n c	Size	1/3 inch interline transfer CCD	
	Scanning System	2:1 Interlace	
E L E C T R I C	Synchronization	INT/LL Selectable 0~359° (Adjustable)	INT/LL Selectable 0~359° (Adjustable)
	Frequency	Horiz: 15.734KHz Vert: 59.94Hz	Horiz: 15.625KHz Vert: 50.00Hz
A L	Resolution	540 TV Lines (Color), 570 TV Lines (BW)	
	Video Output	1.0Vp-p (Video 0.714Vp-ps Sync 0.286Vp-p)	1.0Vp-p (Video 0.7 Vp-p Sync 0.3Vp-p)
T R I C L	S/N (Y signal)	50dB (ACGC Off)	
	Min. Illumination	0Lux with IR LED (27 pcs)	
C L	Gain Control	OFF / LOW / MIDDLE / HIGH	
	White Control	ATW / AWC / MANUAL (1,800°K~10,500°K)	
E L	Electronic Shutter Speed	AUTO / MANUAL (1/60~1/120,000)	AUTO / MANUAL (1/50~1/120,000)
	Sens-Up	OFF / AUTO	
A L	O.S.D	Built-in	
	Motion Detection	ON / OFF (4 Programmable Zone)	
T R I C L	DNR	OFF / LOW / MIDDLE / HIGH (Noise Reduction)	
	Mirror	Built-in (Horizontal Image Inversion)	
E L	Privacy Function	ON / OFF (4 Programmable Zone)	
	Operating Temperature/Humidity	-10°~+50°C / 30~90% RH	
T R I C L	Weight	650g	

Authorized Dealer: